

Express Mail No.: EV355034276US

APPLICATION FOR UNITED STATES PATENT

Title: APPARATUS FOR DISPENSING FREE-FLOWING
MATERIAL

Applicants: Ralf Dittmann, Alfred Luger and Muenuer Menekse

Assignee: Nordson Corporation

**MARKED-UP COPY OF SUBSTITUTE SPECIFICATION SUBMITTED
FOR EXAMINER UNDER MPEP § 608.01(q)
- DO NOT ENTER -**

Kevin G. Rooney
Wood, Herron & Evans, L.L.P.
2700 Carew Tower
441 Vine Street
Cincinnati, OH 45202-2717
Attorneys
(513) 241-2324
Our Ref. No.: NOR-1151

APPARATUS FOR DISPENSING FREE-FLOWING MATERIAL

Field of the Invention

The present invention relates to a device for dispensing free-flowing material and, in particular for dispensing thermoplastic material[, comprising a frame, a container for receiving the material, and a pump connected to the container for conveying the material to a connection from which free-flowing material can be dispensed, wherein the pump has at least one rotatable pump element that can be driven by a rotatable drive shaft, and a drive motor and a coupling disposed between the drive shaft and the drive motor].

Background of the Invention

Devices of this kind for dispensing material, in particular thermoplastic material such as hot melt adhesive, are known in various embodiments. For example, in one embodiment the material to be dispensed is first filled into the container in a solid state, and then melted [therein by heating means and thus brought] to a free-flowing state. The free-flowing material is then channeled from the container to a pump and from there to a connection point that can be connected to at least one tube for further conveying the molten material.

The container, the pump and the drive motor are mounted onto the frame or rack of the apparatus in such a way that the pump, the coupling and the drive motor are arranged in series underneath the container and housed inside a cabinet attached to the frame.

A number of problems arise as a result of this arrangement.

When assembling the pump, the coupling and the drive motor, it is necessary to ensure at all times that the drive shaft of the drive motor and the drive shaft of the pump are precisely aligned with each other, which is a time-consuming affair and often almost impossible due to the manufacturing tolerances of the components and fixing elements. Furthermore, thermally induced effects [induced] brought about by the relatively intensive heating of some components [by the heating means] cause melting of the material, deformations of the components and thermal [distorsions] distortions that lead to a misalignment of the [driven and the] drive shafts of the drive motor and the pump. In the prior art, this has often exposed the shafts and bearings to considerable [mechanial] mechanical and dynamic stress, for example to high bending moments that have led, in turn, to greater wear, especially of bearings. Due to these factors, it was often necessary to replace the pump, the drive motor, or the coupling [or the drive motor] between the pump and the motor with new components. Considerable costs were incurred as a consequence.

The object of the present invention is therefore to avoid the disadvantages of the prior art to a considerable extent and to provide an apparatus for dispensing free-flowing material that is simpler to assemble and disassemble, and that leads to less wear.

Summary of the Invention

[The invention achieves this object in an apparatus of the kind specified at the outset by virtue of the coupling being] Generally, the present invention provides a coupling which is radially detachable[, in relation to the rotational axis of the drive shaft,] from the drive shaft for driving the pump.

[The] An advantage[s] of the invention [mainly consist in the fact that, owing to the special design of the coupling, in particular with a detachably attached coupling element,] is that the drive shaft for driving the pump is radially detachable from the coupling and can also be inserted radially into the coupling during assembly. Assembly and disassembly are thus considerably simplified, because it is no longer necessary[, as hitherto in the prior art,] to disassemble the entire drivetrain comprising the drive motor, the coupling and the pump. Instead, the coupling can be simply detached.

According to another aspect of the invention or a preferred embodiment thereof, it is proposed that the coupling be configured in such a way that an axial offset and/or an angled offset is possible during operation between a shaft of the drive motor and the drive shaft for driving the pump. Assembly and disassembly are further simplified with such a coupling[, because precise [adjustment so that] alignment of the shaft of the pump and the drive motor [are exactly in line is now] is no longer necessary. Furthermore, the coupling easily compensates for any angular or axially parallel offset of the shafts in relation to each other that may result

from thermal expansion. The coupling avoids any lateral forces or bending moments being exerted on the shafts[,] [with the result that] This reduces wear on the bearings and extends service life [is substantially reduced and hence that the service life is extended].

It is preferred that the coupling has a detachably attached coupling element, such that when the coupling element is detached, the coupling of the drive shaft is radially detachable from the drive shaft, or the drive shaft is radially detachable from the coupling. One particularly simple design is obtained when the coupling has a ring element surrounding the drive shaft for driving the pump[, said ring element comprising] The ring element can include two ring segments that are completely separable from each other. The ring segments can be easily separated from or joined to each other.

Other advantageous embodiments of the invention are described below [in the subclaims].

Brief Description of the Invention

The invention will now be described on the basis of an embodiment and with reference to the drawings. [The drawings show:]

Figure 1 is a perspective view of an apparatus according to the invention for melting and dispensing free-flowing material[, in a perspective view].

Figure 2 is a side elevation view of a portion of the apparatus in Figure 1[, in a side elevation view].

Figure 3 is a plan view of the portion shown in Figure 2[, in a plan view, and] .

Figure 4 is a partial section of a coupling in side elevation view [and] .

Figure 5 is a cross-section of the coupling pursuant to Figure 4.

Detailed Description of the Preferred Embodiment

The preferred embodiment shown in the Figures is an apparatus for dispensing thermoplastic material, in particular hot melt adhesive. The separate components of the apparatus are supported by a frame 2 that can be moved by a total of four rollers 4. Each roller is attached to one corner of a parallelepipedal base 6 of frame 2. Also attached to frame 2 are outer walls and doors, as well as a control and regulation unit 8 with an operating and display panel 8.

As Figures 2 and 3 show, a container 10 for receiving the material is disposed inside a portion of the apparatus – on the right in Figure 1 – and can be filled through an upper inlet opening with the material, which can initially be in a solid state, for example in the form of pellets or the like. [The heating means assigned to the container 10 serves to heat and melt the material present in the container. The heating means comprises a) An electrically heated grid 14 is disposed in an upper pre-heating area 12 of container 10 (see Figure 3)[, said grid being electrically heatable]. [The heating means further comprises an] An

electrically heatable melter group 16 is also disposed in the lower portion of the container 10, [said melter group also having] The melter group 16 includes heatable surfaces that can be brought into contact with the material to be melted in order to make the material completely free-flowing and be able to heat it up to a particular temperature. A tube manifold block 18 is disposed underneath the melter group 16, and a plurality of channels for further conveying the free-flowing material is disposed inside [said] the tube manifold block 18. Two safety valve blocks 20 are screwed onto the tube manifold block 18, [and screwed onto said valve blocks there are] Two [two] pumps 22 are fastened to the tube manifold block 18 for conveying the material under pressure through the valve block 20 and the tube manifold block 18 to at least one [connecting piece] port or connection 24, to which at least one tube (not shown) can be connected for further conveying the molten material to the point of application. Inside the tube manifold block 18 and valve blocks 20, but not shown in the Figures, there are channels for the free-flowing material so that material is conveyed from the container 10 to the pump 22 and through the valve blocks 20 and the tube in the manifold block 18 to the one connection or port 24 or to a plurality of connections or ports 24 (see also Figure 2).

Pumps 22 are configured as gear pumps and are each fitted with a drive shaft 26 so that they are able to rotatably drive at least one rotatable pump element, not shown, which in the embodiment comprises two intermeshing gear wheels.

A coupling 28 is joined on the one side to each drive shaft 26 and on the other side to a gearbox 30. [, said gearbox having] The gearbox 30 includes its own drive shaft 32. Each gearbox 30 is flange-mounted to a drive motor 34 configured as an electric motor. Drive motors 34, for their part, are mounted on a portion of frame 2. Gearboxes 30 are supported by an elbow connector 36 that is also attached to a portion of frame 2. The two electric motors 34 can partly be seen in Figure 1.

Coupling 28 of the invention is shown in enlarged form in Figures 4 and 5 and comprises several coupling elements. Couplings 28 may, for example, be Semiflex (registered trademark) couplings from the NFB SD series, which are sold and commercially available from Schmidt-Kupplung GmbH, Am Rehmanager 9, D-38304 Wolfenbüttel, Germany. When the couplings 28 are configured as described below [in the following], they can be radially detached, in relation to the rotational axis of drive shaft 26, from the drive shafts 26 for driving the pumps 22. This is made possible by the couplings 26 having a two-part ring 42 comprised of two ring [elements] segments 38, 40. The two ring segments 38, 40 are detachably attached to each other by two threaded bolts 44 and can be entirely separated from each other. In the center of ring 42 there is a bore 46 into which the drive shaft 26 of pump 22 projects in the assembled state. When threaded bolts 44 are firmly tightened, a frictional connection is formed between ring 42 of coupling 28 such that a torque can be transferred. By loosening threaded bolts 44, the two ring segments 38, 40 can be completely detached from each other in such a way that the

coupling can be radially detached from the respective drive shaft 26. This enables simple assembly and disassembly of pumps 22, without having to entirely disassemble coupling 28 and also drive motor 34 and gearbox 30.

Coupling 28 is also configured in such a way that an axial offset and/or an angled offset is possible during operation, and also during assembly and disassembly, between the drive shaft 32 of gearbox 30, or of a drive motor 34 if there is no gearbox inbetween, and drive shaft 26, such that drive shafts 32 and 26 do not have to be precisely aligned with each other. Axial or angular offsets arising from thermal effects, in particular, can thus be compensated with the help of the coupling. For this purpose, coupling 28 comprises, in addition to ring 42, additional rings 48, 50 that are movable relative to each other and coupled in a substantially torsionally stiff manner by means of pins 52, yet permit angular movements relative to each other as well as axial offset. Coupling pins 52 co-operate with recesses provided in ring 48. For details, reference is made to the Semiflex couplings.

We claim:

Claims

1. Apparatus for dispensing free-flowing material, in particular thermoplastic material, comprising
 - a frame,
 - a container for receiving the material,
 - a pump connected to the container for conveying the material to a connection from which free-flowing material can be dispensed, wherein the pump has at least one rotatable pump element that can be driven by a rotatable drive shaft, and
 - a drive motor, and
 - a coupling disposed between the drive shaft and the drive motor, **characterized in that** the coupling is radially detachable, in relation to the rotational axis of the drive shaft, from the drive shaft for driving the pump.
2. Apparatus according to claim 1 or the generic part of claim 1, characterized in that the coupling is configured in such a way that an axial offset and/or an angled offset is possible during operation between a shaft of the drive motor and the drive shaft for driving the pump.
3. Apparatus according to claim 1 or 2, characterized in that the coupling has a detachably attached coupling element such that when the coupling element is detached, the coupling of the drive shaft is radially

detachable from the drive shaft, or the drive shaft is radially detachable from the coupling.

4. Apparatus according to claim 1 or 2, characterized in that the coupling has a ring element surrounding the drive shaft for driving the pump, said ring element comprising two ring segments that are completely separable from each other.

5. Apparatus according to claim 3, characterized in that two half-rings can be detachably attached to each other.

6. Apparatus according to one of the preceding claims, characterized in that the drive motor is an electric motor with a gearbox coupled thereto for reducing the rotational speed.

7. Apparatus according to one of the preceding claims, characterized in that the pump is a gear pump and is mounted on a pump block of the apparatus.

8. Apparatus according to one of the preceding claims, characterized in that heating means assigned to the container for melting material stored in said container is provided in order to bring the material to a free-flowing state.

9. Apparatus according to one of the preceding claims, characterized in that two independently drivable pumps are provided that can each be driven by couplings and drive motors.

10. Apparatus according to one of the preceding claims, characterized in that the frame has wheels.

APPARATUS FOR DISPENSING FREE-FLOWING MATERIAL

Abstract of the Disclosure

Apparatus for dispensing a free-flowing material comprising a container for receiving the material, a pump connected to the container for conveying the material to a port from which free-flowing material can be dispensed. The pump includes at least one rotatable pump element and a rotatable drive shaft coupled to the pump element, a drive motor, and a coupling attached between the drive shaft and the drive motor. The coupling is radially detachable from the drive shaft.